

**ARCA 604021**

**Order symbol:** ARCA 604021  
**Product nbr:** 8120012  
**Description:** Cabinet, PC  
**Remarks:** 2-point locking

**EAN:** 6418074079237  
**EI. number:**  
 Finland: 3423100  
 Electric No. 8212091100  
 Denmark:  
 Electric No. Sweden: 2500118



Sample photo

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	600	400	210	MPP ARCA 6040
inch:	23.6	15.7	8.3	MPMP ARCA 6040

Materials:	
<b>Material:</b>	Polycarbonate
<b>Base colour:</b>	RAL 7035 -light grey
<b>Cover colour:</b>	RAL 7035 -light grey
<b>Gasket material:</b>	Polyurethane

Temperatures:	
<b>Temperature °C (short term):</b>	-40 ... 120 °C
<b>Temperature °C (continuous):</b>	-40 ... 80 °C
<b>Temperature °F (short term):</b>	-40 ... 250 °F
<b>Temperature °F (continuous):</b>	-40 ... 175 °F

Accessories:	
MPS ARCA 6040	Mounting plate (550x350x2 mm)

MPX ARCA 6040	Mounting plate perforated (550x350x2 mm - 26x11 mm)
DRS ARCA 604021	Mounting plate multiperforated (550x350x2 mm - □3.6 mm)
DRS ARCA 604030	Mounting plate (550x350 mm)
IDS ARCA 6040	DIN rail frame set
PMK ARCA 40	DIN rail frame set
RCS ARCA 6040	Inner door set
SBK ARCA 40	Pole mounting kit
SBK ARCA 60	Rain canopy set
DSP ARCA VLS	Support bar kit
DSP ARCA VRS	Support bar kit
	Door stopper ARCA, vertical, left, small
	Door stopper ARCA, vertical, right, small

Rating:
Ingress Protection (EN 60529): IP66
Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 746C 5V
Glow Wire Test (IEC 695-2-1) °C: 960

**Certificates:**

SGS Fimko  
Gost R

