

# D-SUB STRAIGHT PCB SOCKET CONNECTOR



## 8011 SERIES. D Sub socket connector.

### General Features

- Available in 9, 15, 25, 37 and 50 ways
- Contact area: selective gold plating over nickel
- Solder area: tin plating over nickel
- Different hardware options. Contact sales office

### Materials

- Insulator: Glass-Filled Thermoplastic PBT, UL94V-0 rated
- Contact: Brass
- Shell : Steel, 100U Tin Over 50U Min Copper
- Clinch Nut : Brass, Nickel Plated
- Screwlock : Brass, Nickel Plated
- Operating temperature. -25°C to +85°C
- RoHS compliant

### Dimension Information

### Electrical Features

- Voltage rating: < 250 V
- Current rating: < 3 A
- Contact resistance: < 20 mΩ
- Dielectric withstanding Voltage: 500 V AC/minute
- Insulation resistance: >1000 MΩ

### Mechanical Features

- Insertion force per contact: < 0.34 Kgf
- Withdrawal force per contact: < 0.030 Kgf
- Durability: 500 Cycles

CIRCUITOS	CÓDIGO	DIMENSIONES			
		A	B	C	D
9	8011 – T09C	16.33(0.643)	24.99 (0.984)	30.81 (1.213)	19.23 (0.757)
15	8011 – T15C	24.66 (0.971)	33.32 (1.312)	39.14 (1.541)	27.56 (1.085)
25	8011 – T25C	38.38 (1.511)	47.04 (1.852)	53.04 (2.088)	41.28 (1.625)
37	8011 – T37C	54.84 (2.159)	63.50 (2.500)	69.32 (2.729)	57.73 (2.273)
50	8011 – T50C	52.43 (2.064)	61.11 (2.406)	66.93 (2.635)	55.12 (2.170)

### T = Contact Plating

- T = 3. Gold flash over 50µ" nickel.
- T = 4. 10µ" gold over 50µ" nickel
- T = 5. 15µ" gold over 50µ" nickel
- T = 6. 30µ" gold over 50µ" nickel

### C = Hardware Options

- C = 1. Standard with 3.05mm(.012") dia. mount hole
- C = 3. Whit riveted #4-40 UNC clinch nuts 6.00mm thickness T2
- C = 4. Whit riveted retaining clip ground strap 5.00mm thickness T1
- C = 5. With 4.40 UNC hexagonal standoff D2

