

# MAGNETIC CONTACTS



## EMPS

### Features:

- Reduced Service Calls and False Alarms
- Quality Construction
- Easy, Quick Installation
- Low Investment, High Profit

### Ordering

### Specifications:

EMPS Series:

Magnetic contacts 4 wires (includes a tamper loop)

Feature	EMPS 50 Grey	EMPS 75 White	EMPS 85 White
Mounting style	Overhead door	Recessed; flanges for easier mounting, 5 screw terminals	Surface mount; 5 screw terminals
Dimensions (switch)	49 x 105 x 9.5mm (HxWxD)	20 x 25mm (Ø x 1)	64 x 14 x 12mm (HxWxD)
Dimensions (magnet)	38 x 89 x 38 (HxWxD)	20 x 25mm (Ø x 1)	64 x 14 x 12mm (HxWxD)
Gap distance	55mm	20mm	20mm
Wires	22 AWG, 750mm long (620mm in armoured cable)	-	-
Housing	Die cast aluminium	ABS plastic	
Approvals	EN50131-1 Security Grade 2, Environmental Class II	EN50131-1 Security Grade 1, Environmental Class II	

**Honeywell Security & Custom Electronics**

Newhouse Industrial Estate

Motherwell

Lanarkshire

ML1 5SB

Tel +44 (0)1698 738200

Fax +44 (0)1698 738300

Literature +44 (0)870 240 3387

[www.honeywell.com/security/uk/intruder](http://www.honeywell.com/security/uk/intruder)

**To reorder this literature,**  
**call +44 (0)870 240 3387 quoting ref:**  
HSCE-MAGCONTACT-02-EN(0906)DC-C  
September 2006  
© 2006 Honeywell International Inc.

**Honeywell**