



△△ SPECIFICATION
 Current:3A
 Operation Temperature:-55°C~+105°C
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Withstanding Voltage:1000V AC RMS
 Housing:PBT(UL94V-0),Black
 Contact:Brass,Gold Flash Over Nickel
 No. Of Contacts:04~80 Contacts
 RoHS Compliant

△ H R 2 X XX - H
 (1)(2)(3) (4) (5)

(1) H:2.54 Pin Header
 (2) R:DIP Right Angle
 (3) 2: Dual Row
 (4) XX:No. Of Position/Per Row
 (5) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY EMILY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG. ±5°
PART No. HR2XXX-H		CHECKED BY HZF		
DRAWING No. HR2XXX-H		DRAWING BY HAO		
SCALE NONE	REV. A2	UNIT mm		

NO.	REV.	REVISIONS	CHK	DATE
△2	A2	Modify Data	HZF	12/08/2014
△1	A1	Modify Data	HZF	10/12/2010
△0	A0	NEW RELEASE	SHIN	03/06/2006