

# SERIES KML 2030/RA

Ø 1,8 mm LED

TYPE (3 LEDs)	EMITTED COLOUR	LUMINOUS INTENSITY			FULL VIEWING ANGLE	FORWARD VOLTAGE (IF = 20 mA)		OPERATING TEMPERATURE	FORWARD CURRENT	
		PEAK	TYP.	IF		TYP.	MAX			
KML 2030/RA - R	RED	700	3.5	10	40	2.0	2.5	- 55 to + 100	20	
KML 2030/RA - Y	YELLOW	590	5.5	10	40	2.1	2.5		20	
KML 2030/RA - G	GREEN	565	5.5	10	40	2.2	2.5		20	
KML 2030/RA - E	ORANGE	625	12.5	10	40	2.0	2.5		20	
KML 2030/RA - S	SUPER RED	625	12.5	10	40	2.0	2.5		20	
KML 2030/RA - M	MULTICOLOURED	Indicate colours from top to bottom (see drawing)								
KML 2030/RA - I	IPER RED	660	90	10	40	1.85	2.5		20	
KML 2030/RA - W	RED	660	80	10	30	1.85	2.5		20	
<b>QUALITY TESTED 100%</b>	<b>DIFFUSED</b>	<b>nm</b>	<b>mod</b>	<b>mA</b>	<b>DEGREE°</b>	<b>V</b>	<b>V</b>	<b>°C</b>	<b>mA</b>	

